

RWA DTR 3004 Performance Specifications:

Pattern Generator

- **Minimum bit cell:** 250psec
- **Absolute position accuracy for any transition:** 5psec (typ) 10psec (max)
- **Precompensation resolution for any transition:** 1psec
- **Jitter at 2Gbit/sec:**
 - Random Pattern, RMS: 2psec
 - Repetitive Pattern, RMS: 2psec
- **Frequency resolution:** better than 1Hz
- **Frequency stability:** ± 2.5 ppm up to 75°C, ± 1 ppm/year
- **Random pattern maximum length:** up to 2Mbit

PRML Chip Integration

- **Data Rate:** up to 4Gbit/s (limited by available commercial PRML chips)
- **PRML chips:** Chips from various manufacturers are supported. New PRML chips can be integrated upon request.
- **Channel Optimization**
- **Wide range of PRML Tests**

Analog Channel

- **Bandwidth:** more than 2GHz at -3dB
- **Flatness:** ± 0.2 dB up to 1GHz, ± 0.5 dB up to 1.8GHz
- **Group delay:** ± 100 psec up to 1GHz, ± 200 ps up to 1.8 GHz
- **Non-linear distortion:** better than 1% (entire bandwidth, nominal level)
- **Minimum pulse width (PW) to be measured:** 170psec
- **Parametric measurement accuracy (entire bandwidth):**
 - TAA: ± 0.5 dB*
 - Pulse width: 3% or 20psec whichever is greater*
 - SNR: ± 0.5 dB
 - Modulation: $\pm 2\%$ *
 - Crest factor: $\pm 2\%$
 - Overwrite: ± 0.2 dB
- **Measurements conditions:** sinewave signal without noise.

Servo Channels

- **Drive Servo Decoder**
- **Guzik Servo Decoder**

Specifications are subject to change without notice.

RWA DTR 3004 Physical Specifications:

Physical

- **Size:** 22.1" x 17.6" x 10.8"
- **Weight:** 46 lbs.
- **Power:** 110 VAC ($\pm 10\%$, 50/60 Hz, 4A approximately)
230 VAC ($\pm 10\%$, 50/60 Hz, 3A approximately)

RWA DTR 3004 Options:

| OPTION | PERFORMANCE |
|---|--|
| Universal Preamplifier 10M | 8Gbit/s write data speed, DC to 4GHz analog bandwidth |
| MR7L Low-Impedance Read/Write Amplifier for TMR heads | 4Gbit/s write data speed, 3GHz analog bandwidth |
| Programmable Octave Filters | 1-2GHz, 0.5-1GHz, 0.25-0.5GHz, 0.125-0.25GHz, 0.05-0.125GHz, and 0.05-0.02GHz |
| Programmable Octave Differentiators | 1-2GHz, 0.5-1GHz, 0.25-0.5GHz, 0.125-0.25GHz, 0.05-0.125GHz, and 0.05-0.02GHz |
| Guzik Servo for Guzik and Non Guzik Spinstands | Guzik Servo Revision 4, Servo writing up to 1,024 sectors, 50 kHz servo sampling rate |
| Drive Servo | Programmable servo decoder for HDD and DTR servo decoding |
| Chip Adapter Interface CAI-4000 | Up to 4 Gbit/sec data rate |
| Spectrum Analyzer SA-960 | Frequency domain tests to 960MHz (Guzik recommends using WDM5000/D5000 Waveform Digitizers for frequency domain tests up to 4-6GHz) |